

**A COMPOSITE PACKAGING MATERIAL HAVING A BASE LAYER OF PAPER
AND AN ATTACHED ADDITIONAL LAYER OR TUBULAR SLEEVE ENVELOPE
OF PLASTIC MATERIAL, PARTICULARLY FOR FOOD PRODUCTS, AND
METHOD FOR OBTAINING IT**

RELATED APPLICATION DATA

This application is a continuation-in-part based on U.S. Patent Appln. No. 09/613,810, filed July 11, 2000, and it claims priority under 35 U.S.C. Section 119 based on Italian Patent Appln. No. RM99 U 000158, filed July 12, 1999. These applications are entirely incorporated herein by reference.

BACKGROUND OF THE INVENTION

This invention broadly relates to packaging materials, and more particularly, it concerns a composite, double component, paper based packaging material, especially useful for packaging food products.

Although this specification should be understood as requiring no restrictive limitations on the use of the disclosed packaging materials, materials produced according to the invention have been found to be particularly useful in the field of packaging materials for the retail sale of food products, particularly single piece and discrete products, such as bacon, cheese, meats, dairy products and like.

As is well known, as a consequence of established general practices, and in order to comply with the increasingly more restrictive and binding hygienical regulations, food products offered for retail sale to the public often are packaged in wrappings consisting of sheets of paper based material that are wrapped around the

09739663-122000

00000000000000000000

Even if it is certainly efficient, this approach always entails use of two materials of different kinds, with the consequent problems of storage, inventory, separate housing compartments and like. Furthermore, the handling of the materials entails an increased risk of contamination of the surfaces contacting the concerned food product.

SUMMARY OF THE INVENTION

It is an object of this invention to improve this kind of packaging materials and to provide a composite double component packaging material that is easy to

Such a tubular sleeve enables that, once the product to be packaged is inserted into the tubular sleeve, the assembly can be rolled or folded while the base paper sheet is outwardly maintained, with a full and complete guarantee that, whichever rolling or folding operation is carried out, the packaged food product will only and exclusively contact the inner surface of the tubular sleeve, and it will never contact the external surface of the tubular sleeve. The food product is even less likely to contact any portion of the paper base sheet.

A sleeve member with an equal or preferably larger transversal dimension than that of the base layer enables one to obtain, by means of a simple longitudinal cutting operation of the sleeve material, a composite double-layer packaging

It also is possible to provide a transversal welding on one end edge of the double component packaging material in order to obtain a bag like package.

BRIEF DESCRIPTION OF THE DRAWINGS

Further details and advantages of this invention will be apparent from the following detailed description with reference to the annexed drawings in which the preferred embodiments are shown by way of illustration and not by way of limitation.

In the drawings:

Figure 1 is a cross-sectional view of a composite double component packaging sheet material according to this invention,

Figure 3 is a perspective view of a package according to the invention containing a food product while it is being folded,

Figure 5 is a plan top view of a different embodiment of the invention having two longitudinal flaps adapted to be glued,

Figure 7 is a perspective view of a composite double-layer packaging sheet material according to the invention having two foldable and overlapping flaps, obtained by longitudinally cutting the sleeve-like second component, the second component having dimensions larger than the corresponding dimensions of the support paper base layer, and

Figure 8 shows a sequence of use of a package having both components longitudinally scored in order to wrap a consumable food product and adapted to divide the package into two separate half portions by a simple tearing operation.

DETAILED DESCRIPTION OF THE INVENTION

Referring now to Figure 1 of the drawings, a first embodiment of this invention comprises a first component 10, comprising a base sheet of paper material, upon which a second component 11 formed as a tubular sleeve of a thin film of plastic material is applied. This second component 11 is a plastic material of a kind approved for use with food products. The tubular sleeve 11 may be made of polyethylene or a similar material, manufactured by conventional extrusion methods. It also may be adhered to the paper base sheet 10 by means of conventional methods and equipment, for instance by gluing.

In this first embodiment, a characterizing feature of the thin film tubular sleeve 11 is that, for convenience of use and functionality reasons, it has a transversal dimension not larger than the base sheet 10, and particularly it can be narrower than the base sheet 10, so as to leave a certain free edge on one or on both sides. Upon introducing the concerned food product into the sleeve, the product is retained in a covered and protected condition. The upper flap of the sleeve 11 performs the same function as that performed by a second separate overposed sheet of plastic material according to the present state of the art as described above.

Referring to Figure 2 of the drawings, the initial step for use of the packaging material is shown, in which the upper flap of the tubular sleeve 11 is slightly lifted so that the food product can be introduced into the sleeve 11.

Figure 3 shows the subsequent step for use in which the package is folded. The folding mode is self-explanatory, but it should be understood that the folding step can also be carried out as a rolling step. Additionally, such folding or rolling

000221 09955769

By referring to Figures 4 and 5, it can be observed that the simplest procedure for hermetically closing the package provides that the longitudinal flaps be folded. In this respect, however, the possibility is to be mentioned for the tubular sleeve 11 to have a longitudinal dimension even smaller than the longitudinal dimension of the base sheet 10, so as to leave one or two free longitudinal edges 12 of the base sheet. Such free edges 12 can be provided with suitable glue stripes, for instance, a pressure responsive or sensitive adhesive, so as to make the hermetical closure operation of the package more immediate and certain, as illustrated in Figure 4. Such pressure responsive or sensitive adhesive glue stripes may be adapted to be protected before use by detachable cover strips, so as to activate the gluing effect only at the desired time. Such adhesives and removable cover strips are conventional and well known to those skilled in the adhesive arts.

As above mentioned, the adhesion between the base sheet 10 and the thin plastic material tubular sleeve 11 overlaid thereupon can be effected by means of any desired method and equipment. It is suggested, however, that the adhesion not extend to the whole contacting surfaces, so as to leave a not adherent peripheral edge designed to aid lifting of the upper flap of the sleeve 11.

The package according to this invention allows for a more prolonged storage of the food product contained therein. This package also has the advantage that it eliminates any possibility that the operator, for instance, an employee at a gastronomy bench, will inadvertently contact the inner surface of the packaging sleeve, thereby providing the possibility of handling the package as a whole with little

Referring to Figure 6 of the drawings, a second embodiment of the invention can be observed. In this embodiment, which should not be construed as limiting or restricting the invention, the sleeve component 11 has a transversal dimension equal to (or substantially equal to) the corresponding transversal dimension of the support base sheet 10, and the sleeve member 11 can be longitudinally cut or torn, at a lateral position, so as to form a free flap 11'. After the flap 11' has been opened and the food product has been laid on the double-layer portion of the packaging sheet (*i.e.*, base sheet 10 and bottom sleeve component 11), the so formed free flap 11' is folded over and laid upon the food product. In this manner, the free flap 11' performs the same function as that performed by the second separate sheet of plastic material according to the state of the art described above.

Referring now to Figure 7 of the drawings, a further embodiment of this invention is illustrated. This embodiment again comprises a first component acting as a support base sheet 10, with a sleeve like second component 11 having a transversal dimension much larger than the corresponding transversal dimension of the support base sheet 10. In this embodiment, however, the sleeve member 11 has been longitudinally cut or torn at about its central position, so as to form two free flaps 13 and 14. After the flaps 13 and 14 have been opened and the food product has been laid on the double-layer portion of the packaging sheet (*i.e.*, on base sheet 10 and bottom sleeve component 11), the so formed free flaps 13 and 14 are folded

Figure 8 shows a sequence of use of a package according to this invention, in which a weakness line has been provided, for instance by scoring, in both components of the package. This embodiment has been found to be very useful for packaging food products intended for extemporaneous consumption, for instance, a hot dog or a piece of pizza. After the food product has been inserted into the package (first stage) and the package has been folded (second stage), rolled up (third stage), and possibly closed at its bottom edge (fourth stage), a half portion of the package can be torn off (fifth stage) at the illustrated scoring lines, so that the other half portion continues acting as a cover for the involved product and only the uncovered portion thereof is accessible for consumption. The remaining half portion of the package then acts like a pocket which enables the contents to be withdrawn by a pushing action exerted on the external side of the package, thereby avoiding any risk of soiling one's hands or contaminating the contents of the package.

It has already been mentioned, but it is now desired to underscore, that the two component package can be transversely welded at one end edge, so as to provide a bag like package.

The preferred embodiments of this invention have been heretofore described, but it should be expressly understood that those skilled in the art can make changes and modifications to the details and to the material compositions, as well as to the thicknesses and the shapes of the packaging materials, without departing from the spirit and scope of this invention as defined in the annexed claims.